

Rohilla, Laxmi Narain; Singh, Dinesh Kumar

Article

Direct normal irradiance predictions using broadband models for Indian stations

Energy Reports

Provided in Cooperation with:

Elsevier

Suggested Citation: Rohilla, Laxmi Narain; Singh, Dinesh Kumar (2020) : Direct normal irradiance predictions using broadband models for Indian stations, Energy Reports, ISSN 2352-4847, Elsevier, Amsterdam, Vol. 6, Iss. 2, pp. 572-576, <https://doi.org/10.1016/j.egy.2019.11.121>

This Version is available at:

<https://hdl.handle.net/10419/243934>

Standard-Nutzungsbedingungen:

Die Dokumente auf EconStor dürfen zu eigenen wissenschaftlichen Zwecken und zum Privatgebrauch gespeichert und kopiert werden.

Sie dürfen die Dokumente nicht für öffentliche oder kommerzielle Zwecke vervielfältigen, öffentlich ausstellen, öffentlich zugänglich machen, vertreiben oder anderweitig nutzen.

Sofern die Verfasser die Dokumente unter Open-Content-Lizenzen (insbesondere CC-Lizenzen) zur Verfügung gestellt haben sollten, gelten abweichend von diesen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Terms of use:

Documents in EconStor may be saved and copied for your personal and scholarly purposes.

You are not to copy documents for public or commercial purposes, to exhibit the documents publicly, to make them publicly available on the internet, or to distribute or otherwise use the documents in public.

If the documents have been made available under an Open Content Licence (especially Creative Commons Licences), you may exercise further usage rights as specified in the indicated licence.



<https://creativecommons.org/licenses/by-nc-nd/4.0/>

The 6th International Conference on Power and Energy Systems Engineering (CPESE 2019),
20–23 September 2019, Okinawa, Japan

Direct normal irradiance predictions using broadband models for Indian stations

Laxmi Narain Rohilla*, Dinesh Kumar Singh

Netaji Subhas University of Technology, Sector-3, Dwarka, New Delhi 110078, India

Received 10 October 2019; accepted 23 November 2019

Available online 14 December 2019

Abstract

In this paper three parametric models CPR2, MLWT2 and REST have been used to compute direct normal irradiance (DNI) for five Indian stations, namely New Delhi, Pune, Jaipur, Kolkata and Mumbai. Computed values of DNI have been compared with measured values in terms of percentage root mean square error (RMSE) and percentage mean bias error (MBE). It is observed that the average percentage RMSE for the year is the minimum for MLWT2 model for Jaipur followed by New Delhi and Pune and the values are 1.67%, 2.33% and 2.49%, respectively. But for coastal stations Kolkata and Mumbai the corresponding minimum values occur for CPR2 model and REST model respectively, and the values are 2.62% and 2.76%, respectively. It shows that MLWT2 model performs better for most of the Indian stations except the coastal stations.

© 2019 Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Peer-review under responsibility of the scientific committee of the 6th International Conference on Power and Energy Systems Engineering (CPESE 2019).

Keywords: Direct normal irradiance; Root mean square error; Mean bias error

1. Introduction

Several authors including [1] has explained in their work that the solar energy systems are more energy efficient under cloudless conditions. Under such conditions, most of the solar radiation is in the form of direct radiation. Many devices, like solar concentrators, use only the direct component of the solar radiation.

Network of direct irradiance measuring stations is rather scarce throughout the world and the same is true for India as well. One way of knowing direct radiation at normal incidence, also called direct normal irradiance (DNI), is to measure global and diffuse radiation on horizontal and then convert these values into DNI, by using zenith angle. Another way is to use a pyrheliometer and measure DNI directly. In India, DNI is measured by using pyrheliometer only at four synoptic hours: 9:30, 11:30, 13:30 and 15:30, and this too at few stations only. There is too much paucity of DNI data in India and this necessitates the development of theoretical models to predict DNI under different atmospheric conditions. In the present work as explained in the earlier work by Narain [1], it has been

* Corresponding author.

E-mail address: lnrohilla@gmail.com (L.N. Rohilla).

<https://doi.org/10.1016/j.egy.2019.11.121>

2352-4847/© 2019 Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Peer-review under responsibility of the scientific committee of the 6th International Conference on Power and Energy Systems Engineering (CPESE 2019).

assumed that there is no cloud cover and predictions are made under different amount of water vapor, ozone content and humidity etc.

Many authors have worked along these lines. Solar radiation models for predicting the average daily and hourly global radiation, beam radiation and diffuse radiation have been reviewed by Power [2]. Parameterization Model C has been discussed by Iqbal [3]. King and Buckius [4] have explained direct solar transmittance for a clear sky, that accurately predicts the variation with fundamental quantities. Direct irradiance model, has been explained by Bird and Hulstrom [5]. The parameterized model for global radiation under partially cloudy skies has been explained by Choudhary [6]. As explained by Kotti et al. [7] that the direct solar irradiance can also be accurately calculated from global and diffuse horizontal irradiance measurements after correcting the diffuse irradiance values. In the study of Muneer et al. [8], Meteorological Radiation Model (MRM) enables computation of horizontal beam and diffuse solar radiation using basic meteorological parameters — hourly dry and wet bulb temperature, atmospheric pressure and bright sunshine duration. Eighteen clear sky broadband models for estimating the DNI in Algeria have been investigated by Benkacali et al. [9]. Solar radiation and illuminance was estimated from the meteorological parameters by Muneer et al. [10]. Power [2] employed the monthly-averaged climate turbidity data of North America and Europe to evaluate the relationships among monthly-averaged observed beam radiation, clear-sky beam irradiance, sunshine duration and, day-length. A hybrid model was designed by Yang et al. [11] for estimating monthly mean daily global radiation by employing hourly-recorded bright sunshine time in Japan. Gueymard [12,13,14] has explained about the prediction of direct solar transmittance and irradiance by using various broadband models and concluded that four models, i.e. multi-layer-weighted transmittance model, version 2 (MLWT2), Yang's model, CPCr2 and reference evaluation of solar transmittance (REST) are showing good agreement with measured values.

In the present study, three models, CPCr2, MLWT2 and REST as proposed by Gueymard [12,13,14] have been selected to compute DNI at different hours and different months of the year, for Indian tropical conditions.

2. Models description

2.1. CPCr2 model

This is the two bands model. The limits of the model have been chosen as 0.29 μm and 2.7 μm . These values approximately correspond to the average sensitivity limits of two widely used pyranometers, the Eppley PSP (0.285–2.8 μm) and the Kipp & Zonen CM6 (0.3–2.5 μm). The cut off wavelength between the UV/visible band, B_1 , and the infrared (IR) band, B_2 , has been set to 0.7 μm . This model has been found to be the best model in earlier studies made by Gueymard [15] and Battle et al. [16]. It is completely described by Gueymard [17]. Even though this model depends on Angstrom's wave exponent α , it has been fixed here at 1.3.

2.2. MLWT2 model

This model is modified version of MLWT1, which was originally developed as both a radiation and turbidity prediction method by Gueymard [12,13,18]. MLWT2 model was based on the relatively new concept of multilayer spectral weighting, which is given by Gueymard [19] and Molineaux and Ineichen [20]. This method avoids the limitations of the Beer–Bouguer–Lambert law when applied to large spectral or broad bands. It requires intricate parameterizations because the transmittance of an atmospheric layer depends on the spectral characteristics of all the layers. This technique guarantees better overall accuracy. It also takes into account the variable effect of circumsolar radiation, which increases with turbidity and air mass. In the current work, all the basic functional form is similar to the original MLWT2 model as explained by Gueymard [12,13], except that the total NO_2 absorption is not taken into account. The equation of MLWT2 model is: $E_{bn} = E_{on} T_{Rg} T_o T_w T_a$. Here E_{bn} , is direct normal irradiance; E_{on} , the extra-terrestrial irradiance (i.e. the solar constant times the sun–earth distance correction factor); T_{Rg} , is the Rayleigh and uniformly mixed gas transmittance; T_o , the ozone transmittance; T_w , the water vapor transmittance and T_a , the aerosol transmittance.

2.3. REST model

This model has been proposed by Gueymard [12,13,14] and its form is as follows: $E_{bn} = E_{on}T_R T_g T_o T_w T_a$. Here E_{bn} , is direct normal irradiance; E_{on} , the extra-terrestrial irradiance (i.e. the solar constant times the sun–earth distance correction factor); T_R , is the Rayleigh transmittance; T_g , the uniformly mixed gas transmittance; T_o , the ozone transmittance; T_w , the water vapor transmittance and T_a , the aerosol transmittance.

3. Meteorological data

Five stations of different climatic conditions have been chosen. The stations chosen are — New Delhi representing composite climate; Kolkata, being highly industrialized, represents highly polluted, warm and humid atmosphere; Jaipur, being a desert station, represents hot and dry climate; Mumbai, being coastal city, represent warm and humid climate; Pune represents moderate climate. The solar radiation data, comprising of monthly mean hourly global and diffuse solar radiation for these Indian stations, have been collected from India Meteorology Department (IMD) Pune, India. Monthly mean values averaged over the year for all the five stations, are shown in Table 1.

Table 1. Geographical and climatic data of five Indian stations used in this study.

		Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Kolkata (2002) [22.65°N, 88.45°E 6 masl]	T_a	20	22	26	29	30	30	29	29	28	27	23	21
	R_H	76	75	73	74	77	80	81	82	80	77	75	74
	O_3	0.24	0.26	0.26	0.27	0.28	0.27	0.26	0.26	0.26	0.25	0.25	0.25
	I_{gh}	11.71	16.34	17.42	19.33	18.81	15.65	14.48	15.02	14.99	15.31	13.49	11.83
Jaipur (1999) [26.93°N, 75.86°E 431 masl]	T_a	16	21	24	30	36	33	30	29	28	28	23	18
	R_H	48	45	26	22	37	41	70	70	52	28	38	43
	O_3	0.26	0.27	0.28	0.29	0.29	0.29	0.28	0.27	0.26	0.25	0.25	0.26
	I_{gh}	15.22	17.26	23.48	26.56	26.20	24.94	18.77	19.94	19.36	17.33	16.02	13.89
Mumbai (2001) [19.12°N, 72.85°E 14 masl]	T_a	21	23	24	26	29	28	27	26	26	25	25	23
	R_H	67	68	72	75	78	81	87	87	86	82	75	71
	O_3	0.24	0.26	0.26	0.27	0.28	0.27	0.26	0.26	0.26	0.25	0.25	0.25
	I_{gh}	17.17	20.71	23.71	24.61	25.02	16.16	14.13	14.32	16.05	15.06	16.17	15.23
New Delhi (1999) [28.63°N, 77.20°E 216 masl]	T_a	15	16	21	27	31	35	34	32	29	26	21	17
	R_H	53	53	54	40	38	56	65	72	54	44	44	54
	O_3	0.26	0.27	0.28	0.29	0.29	0.30	0.28	0.27	0.27	0.26	0.25	0.26
	I_{gh}	10.23	15.05	20.98	23.45	22.71	21.25	18.04	18.88	16.36	14.35	14.49	11.67
Pune (2002) [18.53°N, 73.85°E 559 masl]	T_a	15	16	17	20	22	22	21	20	22	22	19	14
	R_H	48	45	26	22	37	41	70	70	52	28	38	43
	O_3	0.26	0.27	0.28	0.29	0.29	0.29	0.28	0.27	0.26	0.25	0.25	0.26
	I_{gh}	18.72	19.94	23.54	25.92	24.10	16.62	20.37	13.00	20.20	18.81	18.04	16.33

T_a : Monthly mean daily temperature (°C); R_H : Monthly mean daily relative humidity (%); O_3 : Ozone amount (cm).

I_{gh} : Monthly mean daily global radiation (MJ/m² day); masl: meter above sea level.

Global and Diffuse radiation are measured by using thermoelectric pyranometers. These pyranometers are calibrated once a year with reference to the World Radiometric Reference (WRR). The estimated uncertainty in the measured data is about $\pm 5\%$. The values of Angstrom turbidity factor, β , for these locations were computed by Louche et al. [21], by taking Angstrom's wave exponent α as 1.3. Estimation of atmospheric turbidity for Indian locations have been studied by Narain and Garg [22] and Aher and Agashe [23].

The other meteorological data includes monthly mean hourly values of atmospheric pressure, temperature and relative humidity. This data is used to compute the amount of precipitable water in the atmosphere, by using an equation given by Leckner [24]. Data for ozone contents for the studied stations have been taken from [3]. One-year data for each of the five Indian stations was used in this study and the year for each station is shown in Table 1.

4. Results and discussions

A computer program was written to compute hourly value of DNI by using three different models; CPCr2, REST and MLWT2 model, for each of the 5 Indian stations mentioned earlier. The model-computed values have

been compared with the measured values in terms of percentage root mean square error, RMSE (%) and percentage mean bias error, MBE (%), and the results are shown in Table 2. The computations were not performed for the monsoon months, June to September, as during these months it is cloudy.

Table 2. RMSE (%) and MBE (%) of computed DNI with three models, in comparison to measured DNI, for New Delhi (1999), Pune (2002), Jaipur (1999), Kolkata (2002) and Mumbai (2001).

Location	Month	RMSE (%)			MBE (%)		
		REST	MLWT2	CPCR2	REST	MLWT2	CPCR2
New Delhi	Jan	5.76	3.86	3.15	-4.51	-3.26	-2.74
	Feb	3.07	1.06	2.06	-2.33	-0.51	-2.00
	Mar	2.38	1.00	2.73	-1.86	-0.63	-2.72
	Apr	1.46	0.74	2.66	-0.99	-0.50	-2.65
	May	0.92	1.59	2.99	-0.28	-1.39	-2.96
	Oct	3.63	5.74	4.40	-3.00	-5.55	-4.38
	Nov	5.19	2.33	3.19	-4.52	-2.12	-3.16
	Dec	6.63	2.37	2.45	-5.60	-2.09	-2.25
Average		3.63	2.33	2.95	-2.89	-2.01	-2.86
Pune	Jan	3.32	1.90	4.09	-2.82	-1.68	-4.08
	Feb	2.53	1.51	3.97	-2.13	-1.22	-3.95
	Mar	1.87	1.27	3.71	-1.34	-0.88	-3.68
	Apr	1.65	1.52	3.75	-1.10	-1.12	-3.73
	May	2.18	3.76	5.39	-1.99	-3.64	-5.39
	Oct	3.19	4.32	5.57	-2.95	-4.21	-5.55
	Nov	3.73	2.98	4.71	-3.35	-2.83	-4.71
	Dec	3.99	2.67	4.55	-3.62	-2.53	-4.54
Average		2.81	2.49	4.47	-2.41	-2.26	-4.45
Jaipur	Jan	5.72	1.89	3.70	-4.80	-1.61	-3.70
	Feb	3.57	1.19	3.38	-2.93	-0.85	-3.35
	Mar	2.08	0.92	2.85	-1.33	-0.05	-2.81
	Apr	1.47	0.78	2.83	-0.82	-0.04	-2.80
	May	1.30	1.04	3.41	-0.89	-0.77	-3.40
	Oct	3.45	3.05	4.44	-3.04	-2.89	-4.41
	Nov	4.96	2.35	4.00	-4.20	-2.01	-3.97
	Dec	6.65	2.17	3.83	-5.61	-1.88	-3.78
Average		3.65	1.67	3.55	-2.95	-1.26	-3.53
Kolkata	Jan	3.46	3.13	1.43	-1.80	-2.19	-1.19
	Feb	2.40	1.69	1.64	-1.43	-1.25	-1.61
	Mar	1.58	2.97	2.04	-0.04	-2.46	-2.01
	Apr	1.94	5.49	3.55	-0.18	-4.99	-3.43
	May	2.18	7.95	5.12	-0.73	-7.48	-5.06
	Oct	2.73	7.32	3.73	-1.87	-7.16	-3.72
	Nov	3.44	3.38	2.18	-2.61	-3.12	-2.11
	Dec	3.85	2.46	1.25	-2.74	-2.04	-1.17
Average		2.70	4.30	2.62	-1.43	-3.84	-2.54
Mumbai	Jan	3.25	1.83	2.20	-2.57	-1.45	-2.19
	Feb	2.82	1.67	2.44	-2.18	-1.23	-2.39
	Mar	2.18	2.04	2.63	-1.77	-1.82	-2.60
	Apr	1.72	2.86	2.84	-1.37	-2.75	-2.82
	May	1.59	3.56	2.99	-1.26	-3.45	-2.98
	Oct	2.21	6.50	3.87	-1.54	-6.41	-3.82
	Nov	3.19	2.81	2.57	-2.73	-2.59	-2.55
	Dec	5.12	3.50	3.15	-3.70	-2.68	-2.75
Average		2.76	3.09	2.84	-2.14	-2.80	-2.76

Table 2 shows that the minimum RMSE is 0.74% for MLWT2 model, in the month of April, and for New Delhi station. Similarly, table shows that minimum MBE is -0.04% for MLWT2 model, in the month April, for Jaipur.

The negative sign shows that the computed value is underestimated and the quantity shows that DNI computed by MLWT2 model in this month for the mentioned station is much closer to measured value.

The average of percentage RMSE, for the whole year, are the minimum for MLWT2 model and for stations Jaipur, followed by New Delhi and Pune and the minimum values are 1.67, 2.33 and 2.49, respectively. While for Kolkata the corresponding minimum value is in CPCER2 model and the value is 2.62 and for Mumbai the same is in REST model that is 2.76. This behavior is because of the Angstrom's turbidity factor being higher during some of the months for these two stations. Here it is observed that the percentage RMSE is lesser in most of the months for most of the stations in MLWT2 model. This shows the suitability of MLWT2 model for most of the Indian stations.

5. Conclusions

The performances of three models CPCER2, MLWT2 and REST have been studied at five Indian stations viz. New Delhi, Kolkata, Mumbai, Pune and Jaipur. The beam radiation at normal incidence was computed. The computed DNI was compared with measured DNI. For most of the Indian stations, RMSE percentage, averaged over a year, is the minimum for MLWT2 model as compared to, CPCER2 and REST models. This study reveals the best performance of MLWT2 model in Indian conditions.

References

- [1] Narain L. A study on solar radiation computation over india [Dissertation]. New Delhi, India: Indian Institute of Technology; 2010.
- [2] Power HC. Estimating clear-sky beam irradiance from sunshine duration. *Sol Energy* 2001;71:217–24.
- [3] Iqbal M. An introduction to solar radiation. New York: Academic Press; 1983.
- [4] King R, Buckius RO. Direct solar transmittance for a clear sky. *Sol Energy* 1979;22:297–301.
- [5] Bird RE, Hulstrom RL. Review, evaluation and improvement of direct irradiance model. *Trans ASME J Sol Energy Eng* 1981;103(3):182–92.
- [6] Choudhary B. A parametrized model for global insolation under partially cloudy skies. *Sol Energy* 1982;29(6):479–86.
- [7] Kotti MC, Argiriou AA, Kazantzidis AK. Use of shadowband correction models for predicting direct solar irradiance. *Proc AIP Conf* : Pap 2013;1531:107–10.
- [8] Muneer T, Gul M, Kambezidis H. Evaluation of an all-sky meteorological radiation model against long-term measured hourly data. *Energy Convers Manage* 1998;39(3–4):303–17.
- [9] Benkacali S, Haddadi M, Khellaf A. Evaluation of direct solar irradiance from 18 broadband parametric models: case of Algeria. *Renew Energy* 2018;125(C):694–711.
- [10] Muneer M, Gul MS, Kubie J. Models for estimating solar radiation and illuminance from meteorological parameters. *Trans ASME Sol Energy Eng* 2000;122(3):146–53.
- [11] Yang K, Huang GW, Tamai N. A hybrid model for estimating global solar radiation. *Sol Energy* 2001;70(1):13–22.
- [12] Gueymard C. Direct solar transmittance and irradiance predictions with broadband models. Part I: detailed theoretical performance assessment. *Sol Energy* 2003;74:355–79.
- [13] Gueymard C. Direct solar transmittance and irradiance predictions with broadband models. Part II: validation with high quality measurements. *Sol Energy* 2003;74:381–95.
- [14] Gueymard C. Corrigendum to direct solar transmittance and irradiance predictions with broadband models. Part I: detailed theoretical performance assessment. *Sol Energy* 2004;74:513K.
- [15] Gueymard C. Spectral models. In: Gordon J, editor. *Solar energy – the state of the art*. London: James and James Publishers; 2001, p. 527–31.
- [16] Battle FJ, Olmo FJ, Tovar J, Alados-Arboledas L. Comparison of cloudless sky parameterization of solar irradiance at various Spanish mid latitude location. *Theo Appl Climatol* 2000;66:81–93.
- [17] Gueymard C. Two band model for the calculation of clear sky solar irradiance, illuminance, and photosynthetically active radiation at the earth surface. *Sol Energy* 1989;43(5):253–65.
- [18] Gueymard C. Turbidity determination from broadband irradiance measurements. *J Appl Meteorol* 1998;37(4):414–35.
- [19] Gueymard C. Multilayer-weighted transmittance functions for use in broadband irradiance and turbidity calculations. In: Campbell-Howe R, Wilkins-Crowder B, editors. *Proceedings of solar 96, annual conference of the American solar energy society*. Asheville, NC: ASES; 1996, p. 281–6.
- [20] Molineaux B, Ineichen P. On the broad band transmittance of direct irradiance in a cloudless sky and its application to the parameterization of atmospheric turbidity. *Sol Energy* 1996;56(6):553–63.
- [21] Louche A, Maurel M, Simonnot G, Peri G, Iqbal M. Determination of Angstrom's turbidity coefficient from direct total solar irradiance measurements. *Sol Energy* 1987;38:89–96.
- [22] Narain L, Garg SN. Estimation of linke turbidity factors for different regions of India. *Int J Environ Waste Manage* 2013;12(1):52–64.
- [23] Aher GR, Agashe VV. Determination of atmospheric turbidity at Pune. *Indian J Radio Space Phys* 1998;27(2):53–9.
- [24] Leckner B. The spectral distribution of solar radiation at the earth's surface. *Elements of a model*. *Sol Energy* 1978;20(2):143–50.